





Armatures en laiton nickelé



Réductions en laiton nickelé avec filetages coniques

Article	G1	G2	A1	SW1	VP1	VE	VP2
38.580/VK	G 1/4	G 1/8	11 mm	SW14	1.05	50	0.92
38.582/VK	G 3/8	G 1/8	12 mm	SW17	1.25	50	1.10
38.583/VK	G 3/8	G 1/4	12 mm	SW17	1.15	50	1.01
38.585/VK	G 1/2	G 1/8	14 mm	SW22	2.20	25	1.93
38.586/VK	G 1/2	G 1/4	14 mm	SW22	2.00	25	1.75
38.587/VK	G 1/2	G 3/8	14 mm	SW22	1.90	25	1.66
38.591/VK	G 3/4	G 3/8	17 mm	SW27	4.30	25	3.77
38.592/VK	G 3/4	G 1/2	17 mm	SW27	3.25	25	2.85
38.595/VK	G 1	G 3/4	19 mm	SW34	6.80	10	5.98
38.596/VK	G 1	G 1/2	19 mm	SW34	7.50	10	6.62
38.600/VK	G 1 1/4	G 1/2	22 mm	SW45	18.00	10	15.92
38.601/VK	G 1 1/4	G 3/4	22 mm	SW45	18.00	10	15.92
38.602/VK	G 1 1/4	G 1	22 mm	SW45	18.00	10	15.92



Bouchon de fermeture avec six pans

En laiton nickelé avec filetage conique.

Article	G1	A1	A2	SW1	VP1	VE	VP2
43.910/S14	G 1/8	6.5 mm	10 mm	SW14	0.95	100	0.70
43.911/S17	G 1/4	9 mm	13 mm	SW17	1.05	100	0.90
43.912/S19	G 3/8	9.5 mm	13.5 mm	SW19	1.35	100	1.10
43.913/S24	G 1/2	10 mm	14.5 mm	SW24	2.20	100	1.70
43.914/S30	G 3/4	11 mm	16 mm	SW30	3.25	100	2.50