




## Sicherheitsventile für Druckluft




### Klein-Sicherheitsventil, bauteilegeprüft

Jedes Ventil plombiert und gestempelt.

Messing blank mit VITON-Dichtung.

Artikel	G1	Druck	Leistung p + 1 bar	A1	SW1	VP1
40.020.015	G 1/4	1.5 bar	21 m <sup>3</sup> /h	85 mm	SW19	44.50
40.020.04	G 1/4	4 bar	55 m <sup>3</sup> /h	85 mm	SW19	44.50
40.020	G 1/4	6 bar	78 m <sup>3</sup> /h	85 mm	SW19	44.50
40.020.08	G 1/4	8 bar	100 m <sup>3</sup> /h	85 mm	SW19	44.50
40.021	G 1/4	11 bar	133 m <sup>3</sup> /h	85 mm	SW19	44.50
40.020.15	G 1/4	15 bar	128 m <sup>3</sup> /h	85 mm	SW19	44.50
40.025.060	G 3/8	6 bar	156 m <sup>3</sup> /h	85 mm	SW19	44.50
40.026.110	G 3/8	11 bar	267 m <sup>3</sup> /h	85 mm	SW19	44.50



### Sicherheitsventil für Druckluftanlagen

Ventilkörper Rotguss, Dichtung Viton, eingestellt und plombiert.

Kann auch revidiert und neu plombiert werden.

Artikel	G1	Druck	Leistung p + 1 bar	A1	SW1	VP1
40.041.100	G 1/2	10 bar	245 m <sup>3</sup> /h	150 mm	SW26	246.00
40.041.110	G 1/2	11 bar	267 m <sup>3</sup> /h	150 mm	SW26	246.00
40.041.120	G 1/2	12 bar	289 m <sup>3</sup> /h	150 mm	SW26	246.00
40.031.090	G 3/4	9 bar	375 m <sup>3</sup> /h	150 mm	SW32	269.60
40.030.100	G 3/4	10 bar	412 m <sup>3</sup> /h	150 mm	SW32	269.60
40.031.110	G 3/4	11 bar	449 m <sup>3</sup> /h	150 mm	SW32	269.60
40.031.120	G 3/4	12 bar	487 m <sup>3</sup> /h	150 mm	SW32	269.60
40.033.080	G 1	8 bar	758 m <sup>3</sup> /h	200 mm	SW36	294.30
40.033.100	G 1	10 bar	931 m <sup>3</sup> /h	200 mm	SW36	294.30
40.034.110	G 1	11 bar	1015 m <sup>3</sup> /h	200 mm	SW36	294.30