



# Armatures pour tuyaux en laiton doré



## Accouplement à griffes avec raccord pour tuyau

-0.99 / + 6 bar (avec 2 colliers 12.5 bar).


Article	A4	VP1	VE	VP2
51.728	LW 13	7.20	10	5.60
51.729	LW 16	9.70	10	6.80
51.730	LW 20	8.80	10	6.40
51.731	LW 25	9.50	10	7.40
51.732	LW 32	13.30	10	9.40



## Accouplement à griffes avec filetage mâle ou femelle

-0.99 / + 12.5 bar.

Article	G1	VP1	VE	VP2
51.736	G 3/4 femelle	9.60	10	7.40
51.737	G 1 femelle	10.55	10	7.40
51.738	G 1 1/4 femelle	10.55	10	6.90
51.734	G 1/4 mâle	13.30	10	9.40
51.733	G 3/4 mâle	7.20	10	5.60



## Raccord pour tuyaux avec filetage mâle, Laiton doré avec bord

Pour pression voir page T084F.

-20 / +140° C.

Article	G1	A4	A1	A2	D1	D2	Ø	VP1	VE	VP2
40.618	G 3/4	LW 13	40 mm	24 mm	14 mm	11 mm	Ø 28	7.10	100	5.30
40.619	G 3/4	LW 16	45 mm	26 mm	17 mm	13 mm	Ø 28	5.45	100	3.90
51.621	G 1	LW 19	42.5 mm	28 mm	21 mm	16 mm	Ø 37	8.85	100	6.60
51.624	G 1	LW 38	59 mm	47 mm	41 mm	27 mm	Ø 41	24.55	100	18.30
40.624	G 1 1/4	LW 25	52 mm	35 mm	27.5 mm	21 mm	Ø 47	17.60	100	14.90
40.634	G 1 1/2	LW 32	68 mm	39 mm	33 mm	27 mm	Ø 55	31.45	100	22.50
40.639	G 2	LW 38	69 mm	47 mm	41 mm	34 mm	Ø 65	43.80	100	34.80
51.626	G 1 1/4	LW 38	64 mm	47 mm	41 mm	33 mm	Ø 47	26.10	100	22.10