




# Schlauchanschlüsse Stahl verzinkt



Schlauchanschluss Stahl verzinkt mit zylindrischem Aussengewinde

Druck für Flüssigkeiten bis 20 bar, für Druckluft bis 15 bar.

-20 / +140° C.

Artikel	G1	Für Schlauch	A1	A2	D1	D2	SW1	VP1
40.590	G 1/8	LW 4 mm	38.5 mm	27.5 mm	5 mm	2 mm	SW12	3.75
40.620	G 1/8	LW 6 mm	34.5 mm	23.5 mm	7 mm	3 mm	SW12	2.30
40.621	G 1/8	LW 8 mm	38.5 mm	27.5 mm	9 mm	5 mm	SW12	2.50
40.622	G 1/8	LW 10 mm	42.5 mm	27.5 mm	11 mm	5 mm	SW16	2.30
40.591	G 1/4	LW 4 mm	38.5 mm	23.5 mm	5 mm	2 mm	SW16	2.85
40.625	G 1/4	LW 6 mm	38.5 mm	23.5 mm	7 mm	3 mm	SW16	2.20
40.626	G 1/4	LW 8 mm	38.5 mm	23.5 mm	9 mm	5 mm	SW16	2.20
40.627	G 1/4	LW 10 mm	38.5 mm	23.5 mm	11 mm	7 mm	SW16	2.20
40.628	G 1/4	LW 13 mm	42.5 mm	27.5 mm	13 mm	8 mm	SW16	2.40
40.630	G 3/8	LW 8 mm	41 mm	23.5 mm	9 mm	5 mm	SW22	3.65
40.631	G 3/8	LW 10 mm	41 mm	23.5 mm	11 mm	7 mm	SW22	3.65
40.632	G 3/8	LW 13 mm	45 mm	27.5 mm	13 mm	8 mm	SW22	3.95
40.633	G 3/8	LW 16 mm	58 mm	40 mm	16.5 mm	10 mm	SW22	4.20
40.635	G 1/2	LW 16 mm	59 mm	40 mm	16.5 mm	10 mm	SW25	6.55
40.636	G 1/2	LW 19 mm	59 mm	40 mm	20 mm	13 mm	SW25	6.70
40.637	G 3/4	LW 19 mm	59 mm	40 mm	20 mm	13 mm	SW30	7.10