



Schlaucharmaturen aus Messing blank



Klauenkupplung mit Schlauchanschluss

-0.99 / + 6 bar (mit 2 Klemmen bis 12.5 bar).


Artikel	Für Schlauch	VP1	VE	VP2
51.728	LW 13 mm	7.20	10	5.60
51.729	LW 16 mm	9.70	10	6.80
51.730	LW 20 mm	8.80	10	6.40
51.731	LW 25 mm	9.50	10	7.40
51.732	LW 32 mm	13.30	10	9.40



Klauenkupplung mit Gewinde aussen oder innen

-0.99 / + 12.5 bar.

Artikel	G1	VP1	VE	VP2
51.736	G 3/4 innen	9.60	10	7.40
51.737	G 1 innen	10.55	10	7.40
51.738	G 1 1/4 innen	10.55	10	6.90
51.734	G 1/4 aussen	13.30	10	9.40
51.733	G 3/4 aussen	7.20	10	5.60



Schlauchanschluss mit zylindrischem Aussengewinde, Messing blank

Ausführung mit Bund.

-20 / +140° C.

Artikel	G1	Für Schlauch	A1	A2	D1	D2	Ø	VP1	VE	VP2
40.618	G 3/4	LW 13 mm	40 mm	24 mm	14 mm	11 mm	Ø 28	7.10	100	5.30
40.619	G 3/4	LW 16 mm	45 mm	26 mm	17 mm	13 mm	Ø 28	5.45	100	3.90
51.621	G 1	LW 19 mm	42.5 mm	28 mm	21 mm	16 mm	Ø 37	8.85	100	6.60
51.624	G 1	LW 38 mm	59 mm	47 mm	41 mm	27 mm	Ø 41	24.55	100	18.30
40.624	G 1 1/4	LW 25 mm	52 mm	35 mm	27.5 mm	21 mm	Ø 47	17.60	100	14.90
40.634	G 1 1/2	LW 32 mm	68 mm	39 mm	33 mm	27 mm	Ø 55	31.45	100	22.50
40.639	G 2	LW 38 mm	69 mm	47 mm	41 mm	34 mm	Ø 65	43.80	100	34.80
51.626	G 1 1/4	LW 38 mm	64 mm	47 mm	41 mm	33 mm	Ø 47	26.10	100	22.10