




# Raccords pour tuyaux en L, polyamide 66



Raccord pour tuyaux bleu en équerre, filetage mâle conique

Pour une pression de -0.99 à 12.5 bar à 25° C.

Pour air comprimé, vacuum, eau, huiles et émulsions.

Article	G1	Pour tuyau int.	A1	A2	D1	SW1	VP1	VE	VP2
38.210	G 1/8	LW 4	22 mm	22.5 mm	5 mm	SW11	1.05	100	0.92
38.220	G 1/8	LW 6	24 mm	31 mm	7 mm	SW11	1.05	100	0.92
38.221	G 1/8	LW 8	26 mm	36 mm	9 mm	SW11	1.15	100	1.01
38.211	G 1/4	LW 4	24 mm	22.5 mm	5 mm	SW14	1.05	100	0.92
38.225	G 1/4	LW 6	26 mm	31 mm	7 mm	SW14	1.15	100	1.01
38.226	G 1/4	LW 8	28 mm	36 mm	9 mm	SW14	1.25	100	1.10
38.227	G 1/4	LW 10	28 mm	39 mm	11 mm	SW14	1.35	100	1.20
38.228	G 1/4	LW 13	28 mm	41 mm	13 mm	SW14	1.50	100	1.29
38.229	G 3/8	LW 6	26 mm	31 mm	7 mm	SW17	1.35	100	1.20
38.230	G 3/8	LW 8	28 mm	26 mm	9 mm	SW17	1.35	100	1.20
38.231	G 3/8	LW 10	28 mm	39 mm	11 mm	SW17	1.60	100	1.38
38.232	G 3/8	LW 13	28 mm	41 mm	13 mm	SW17	1.50	100	1.29
38.248	G 1/2	LW 8	30.5 mm	36 mm	9 mm	SW22	1.35	50	1.20
38.249	G 1/2	LW 10	30.5 mm	39 mm	11 mm	SW22	1.50	50	1.29
38.234	G 1/2	LW 13	30.5 mm	41 mm	13 mm	SW22	1.60	50	1.38
38.235	G 1/2	LW 16	36 mm	44 mm	17 mm	SW22	1.80	50	1.56
38.236	G 1/2	LW 19	36 mm	45 mm	20 mm	SW22	1.80	50	1.56
38.237	G 3/4	LW 13	31.5 mm	41 mm	13 mm	SW27	1.60	50	1.38
38.238	G 3/4	LW 16	37 mm	44 mm	17 mm	SW27	2.20	50	1.93
38.239	G 3/4	LW 19	37 mm	45 mm	20 mm	SW27	2.20	50	1.93