




Raccords pour tuyaux en laiton nickelé



Raccord pour tuyaux avec filetage mâle conique

Exécution courte, -0.99 / +12.5 bar.

-20 / +140° C.

Article	G1	Pour tuyau int.	A1	D1	D2	SW1	VP1	VE	VP2
38.470	G 1/8	LW 6	32 mm	7 mm	4.5 mm	SW12	1.35	100	1.00
38.471	G 1/8	LW 8	32 mm	9 mm	5.5 mm	SW12	1.35	100	1.00
38.472	G 1/4	LW 6	35.5 mm	7 mm	4.5 mm	SW14	1.35	100	1.10
38.485	G 1/4	LW 7	35.5 mm	8 mm	5.5 mm	SW14	1.60	100	1.10
38.473	G 1/4	LW 8	35.5 mm	9 mm	6.5 mm	SW14	1.60	100	1.20
38.474	G 1/4	LW 10	35.5 mm	12 mm	9 mm	SW14	1.60	100	1.20
38.475	G 3/8	LW 8	36 mm	9 mm	6.5 mm	SW17	2.30	100	1.70
38.476	G 3/8	LW 10	36 mm	12 mm	9.5 mm	SW17	2.30	100	1.70
38.477	G 3/8	LW 13	36 mm	14 mm	10 mm	SW17	2.30	100	1.70
38.478	G 3/8	LW 16	36 mm	17 mm	12 mm	SW17	2.40	100	1.80
38.479	G 3/8	LW 19	36 mm	21 mm	16 mm	SW17	3.65	100	2.70
38.480	G 1/2	LW 8	39 mm	9 mm	6.5 mm	SW22	3.25	100	2.30
38.486	G 1/2	LW 9	37 mm	10 mm	7 mm	SW22	3.25	100	2.30
38.481	G 1/2	LW 10	39 mm	12 mm	9.5 mm	SW22	3.25	100	2.30
38.482	G 1/2	LW 13	39 mm	14 mm	10.5 mm	SW22	3.35	100	2.50
38.483	G 1/2	LW 16	39 mm	17 mm	13.5 mm	SW22	3.35	100	2.50
38.484	G 1/2	LW 19	39 mm	20 mm	15 mm	SW22	3.65	100	2.70