



Gummi-Druckschläuche



Druckluftschlauch aus Naturgummi

Blau oder rot, auch Autogenschlauch genannt.

Sehr flexibel.

Achtung: nicht im Öl liegen lassen.

Artikel	D1 innen	D2 aussen	P1 Max. 40° C	Farbe	VP1	VE	VP2
40.500	LW 6 mm	14 mm	15 bar	Blau	4.60	80 m	3.60
40.499	LW 6 mm	14 mm	15 bar	Rot	5.00	60 m	3.90
40.501	LW 8 mm	16 mm	15 bar	Blau	4.60	100 m	3.60
40.498	LW 8 mm	16 mm	15 bar	Rot	6.20	60 m	4.90
40.502	LW 10 mm	19 mm	15 bar	Blau	5.80	60 m	4.60
40.497	LW 10 mm	19 mm	15 bar	Rot	7.00	60 m	5.60



Ölbeständiger Neoprenschauch schwarz

Einsetzbar von -20 / +80° C.

Für Druckluft, Diesel, Öl und Wasser.

Artikel	D1 innen	D2 aussen	P1 Max. 40° C	VP1	VE	VP2
40.505	LW 6 mm	13 mm	16 bar	6.40	50 m	5.00
40.506	LW 8 mm	15 mm	16 bar	7.00	50 m	5.50
40.507	LW 10 mm	17 mm	15 bar	8.10	50 m	6.40
40.503	LW 13 mm	20 mm	12 bar	11.00	50 m	8.70
35.751	LW 16 mm	24 mm	12 bar	13.40	50 m	10.60
35.752	LW 19 mm	29 mm	12 bar	16.50	50 m	13.10
35.753	LW 25 mm	35 mm	10 bar	23.20	40 m	18.40