


## Storz-Festkupplungen mit Außengewinde

**Optional:** drehbarer Außengewindestutzen -DR (nur verfügbar für die mit \* gekennzeichneten Typen)

Typ	Typ	Typ	Rostfrei*	Storz-Größe	Knaggen-abstand	Außen-gewinde
Alu geschmiedet	Messing	1.4581				
H301.5541	H301.5544	H301.5542		25-D	31	G 3/4"
H301.5537	H301.5540	H301.5538		25-D	31	G 1"
H301.5545	H301.5546	---		32	44	G 1"
H301.5547	H301.5548	---		32	44	G 1 1/4"
H301.5551	H301.5552	---		38	52	G 1 1/4"
H301.5549	H301.5550	---		38	52	G 1 1/2"
H301.5553	H301.5555	H301.5554		52-C	66	G 1"
H301.5560	H301.5562	H301.5561		52-C	66	G 1 1/4"
H301.5557	H301.5559	H301.5558		52-C	66	G 1 1/2"
H301.5564	H301.5568	H301.5566		52-C	66	G 2"
H301.5570	H301.5572	H301.5571		65	81	G 2"
H301.5574	H301.5576	H301.5575		65	81	G 2 1/2"
H301.5578	H301.5579	---		65	81	G 3"
H301.5581	H301.5584	H301.5583		75-B	89	G 2 1/2"
H301.5586	H301.5588	H301.5587		75-B	89	G 3"
H301.5528	---	---		90	105	G 3"
H301.5530	---	H301.5531		100	115	G 4"
H301.5533	H301.5536	H301.5535		110-A	133	G 4"

**Suchbeispiel:** H301.5541 \*\*




## Storz-Festkupplungen mit Innengewinde

**Werkstoffe:** Dichtungen im Innengewinde: NBR (Typ 1.4581: Teflon)  
**Optional:** drehbarer Innengewindestutzen -DR, mit Verriegelung -VER **NEU**

Typ	Typ	Typ	Rostfrei*	Storz-Größe	Knaggen-abstand	Innen-gewinde
Alu geschmiedet	Messing	1.4581				
H301.5611	H301.5613	H301.5612		25-D	31	G 1/2"
H301.5614	H301.5617	H301.5615		25-D	31	G 3/4"
H301.5607	H301.5610	H301.5608		25-D	31	G 1"
H301.5618	H301.5619	---		32	44	G 1"
H301.5620	H301.5621	---		32	44	G 1 1/4"
H301.5624	H301.5625	---		38	52	G 1 1/4"
H301.5622	H301.5623	---		38	52	G 1 1/2"
H301.5626	H301.5628	H301.5627		52-C	66	G 1"
H301.5634	H301.5637	H301.5636		52-C	66	G 1 1/4"
H301.5629	H301.5633	H301.5631		52-C	66	G 1 1/2"
H301.5639	H301.5644	H301.5641		52-C	66	G 2"
H301.5645	H301.5647	H301.5646		52-C	66	G 2 1/2"
H301.5648	H301.5651	H301.5650		65	81	G 2"
H301.5652	H301.5656	H301.5655		65	81	G 2 1/2"
H301.5657	H301.5659	---		65	81	G 3"
H301.5660	H301.5664	H301.5662		75-B	89	G 2"
H301.5666	H301.5670	H301.5668		75-B	89	G 2 1/2"
H301.5671	H301.5676	H301.5674		75-B	89	G 3"
H301.5589	---	---		90	105	G 3"
H301.5591	H301.5595	H301.5594		100	115	G 4"
H301.5596	H301.5601	H301.5599		110-A	133	G 4"
H301.5602	H301.5605	H301.5604		110-A	133	G 4 1/2"

<sup>1)</sup> DIN 14306, <sup>2)</sup> DIN 14307, <sup>3)</sup> DIN 86204, <sup>4)</sup> DIN 14308, <sup>5)</sup> DIN 86205, <sup>6)</sup> DIN 14309

**Suchbeispiel:** H301.5634 \*\*



Option: mit Verriegelung

## Storz-Übergangsstücke

Typ	Typ	Typ	Rostfrei*	Storz-Größe	Knaggen-abstand 1	Knaggen-abstand 2
Alu geschmiedet	Messing	1.4581				
H301.5514	---	---		38/25-D	52	31
H301.5515	H301.5517	H301.5516		52-C/25-D	66	31
H301.5518	---	---		65/38	81	52
H301.5519	H301.5521	H301.5520		65/52-C	81	66
H301.5522	H301.5524	H301.5523		75-B/52-C	89	66
H301.5525	H301.5527	H301.5526		75-B/65	89	81
H301.5507	---	---		90/75-B	105	89
H301.5509	---	---		100/75-B	115	89
H301.5508	---	---		100/90	115	105
H301.5511	H301.5513	H301.5512		110-A/75-B	133	89
H301.5510	---	---		110-A/100	133	115

<sup>1)</sup> DIN 14341, <sup>2)</sup> DIN 14342, <sup>3)</sup> DIN 14343



Alle Angaben verstehen sich als unverbindliche Richtwerte! Für nicht schriftlich bestätigte Datenauswahl übernehmen wir keine Haftung. Druckangaben beziehen sich, soweit nicht anders angegeben, auf Flüssigkeiten der Gruppe II bei +20°C.